


电感式接近开关 Inductive sensor
EL10X-30YP-AN6-C2



Type EL10X-30YP-AN6-C2
Ident No. 11305011

- Threaded barrel,M30x1.5
- Chrome-plated brass
- 3-wire, 10...30VDC
- cable

技术参数
Technical parameter

电气参数 electrical parameter

Rated switching distance Sn	10 mm
Assured switching distance Sr	≤ (0.81 x Sn) mm
Mounting conditions	flush
Operating voltage	10...30 VDC
Pulsating voltage	≤ 20%
DC rated operational current	≤ 100mA
No-load current	≤ 10mA
Voltage drop at Ie	≤ 2V
Repeatability	≤ 5% Sr
Hysteresis	3...15% Sr
Temperature drift	≤ ±10%
Switching frequency	300 Hz
Output function	3-wire NPN , NO
Short-circuit protection	yes
Reverse polarity protection	yes
Switching state	LED , yellow
Vibration resistance	55Hz (1mm)
Shock resistance	30g (11ms)
IP rating	IP67
Certification	CE

机械参数 mechanical parameter

Dimension	M30x1.5
Housing material	metal,CuZn-Cr
Material active area	PBT
End cap	PA
Max.tightening torque housing nut	25Nm
Connection	cable
Cable quality	PVC , 2m
Cable cross section	3 x 0.34 mm ²
Ambient temperature	-25...70°C

接线图
Wiring diagram

