
Programmable temperature sensor

TB-18MN-DPN6D-SC





Type TB-18MN-DPN6D-SC

Ident No. 070411024

- large size digital tube, rotate 180°.
- The 304 stainless steel housing, the housing can be freely rotated by 330°.
- Three programmable buttons can quickly select and switch the menus.
- The probe length can be customized.

Technical parameter

Electrical parameter

| Mounting conditions | insertion style sensor |
|---|------------------------|
| Operating voltage | 15-30V DC |
| Rated operational current | 200mA |
| Voltage drop at Ie | ≤ 2V |
| No-load current | ≤ 50mA |
| Switch accuracy | 1% |
| Max output current | 500mA |
| Output function | 2xPNP/NPN |
| Max output current | 500mA |
| Liquid medium temperature | -50°C100°C |
| Operating temperature | -25°C80°C |
| Switching point | -49.8°C100°C |
| Release point | -50°C99.8°C |
| Permanent display of termerature unit (°C , °F) | |
| Measure model | hysteresis, window |
| Display | LED digital display |
| Protection classification | IP 65 |

Mechanical parameter

| Housing material | stainless steel(304) |
|-----------------------------------|-----------------------|
| Sensor material | stainless steel(304) |
| Thread connection | external thread M18 |
| Max.tightening torque housing nut | 30Nm |
| Connection | 4 pin M12x1 connector |

Wiring diagram

